



TECHNICAL INFORMATION

THICKNESS	TYPE	APPEARANCE	USES	EXTRAS
6mm is standard (Available from 2mm to 25mm, price increases with thickness)	Clear Float	Transparent Visible green tint with painted back	Painted Splashbacks Textured Feature Panels Windows Shelves Furniture Mirrors Balustrades Shower screens	Can be annealed, heat strengthened, toughened, painted, curved, laminated, metal coated, silvered, sand blasted, drilled, cut out or shaped
Same as "Clear Float"	Tinted Float	Tinted Transparent Colour Available in Grey, Green, Bronze and Blue	Doors and Windows Reducing Glare Reducing Heat Gain Furniture Decorative Feature Panels Can be Textured	Must be toughened to withstand thermal breakage, such as panels situated near stove or in full sun.
6mm is standard	Low Iron "Diamante"	True Clear	Painted Splashbacks (achieves a "true" white) Creates an "Ice" like visual effect on feature Panels.	Low iron glass is more prone to breakage, it must be toughened & has size limitations

Our policy at Glass FX is to toughen all glass panels, this will ensure that every panel is * 5 time stronger than annealed glass
 *Safe in areas affected by heat *Safe against flexing at cutouts (such as powerpoints) * Has a 10 Year Guarantee on workmanship
 * Will avoid replacing panels, then encountering colour match difficulties due to different float glass batches and paint re-mixing.

NOTES: Toughened glass cannot be cut, size and shape must be accurate in advance. Curved glass cannot be toughened.